

ZAWIAS SWW i XWW / DOBÓR ZE WZGLĘDU NA DOPUSZCZALNE OBCIĄŻENIE



Budownictwo prywatne

Budownictwo publiczne




Samozamykacz



Zawias 2-skrzydłowy



Zawias 3-skrzydłowy



W przypadku drzwi o wysokości powyżej 2200mm należy zastosować dodatkowy zawias na środku w celu doszczelnienia skrzydła.

2 x	W \ S	800	900	1000	1100	1200
	+	2000	58	54	50	46
	2100	60	57	53	49	45
	2200	60	60	55	51	47
	2300	60	60	58	54	50
	2400	60	60	60	56	52
	2500	60	60	60	59	55

3 x	W \ S	800	900	1000	1100	1200
	+	2000	99	92	85	79
	2100	104	96	89	83	77
	2200	105	101	94	87	80
	2300	105	105	98	91	84
	2400	105	105	103	96	89
	2500	105	105	105	100	93

2 x	W \ S	800	900	1000	1100	1200
		2000	64	59	55	51
+	2100	67	62	58	53	50
	2200	71	65	61	56	52
	2300	74	69	64	59	55
	2400	75	72	67	62	57
	2500	75	75	70	65	60

3 x	W \ S	800	900	1000	1100	1200
		2000	105	97	90	83
+	2100	110	102	95	88	81
	2200	110	107	99	92	85
	2300	110	110	104	96	89
	2400	110	110	109	101	94
	2500	110	110	110	106	98

2 x	W \ S	800	900	1000	1100	1200
		2000	70	65	60	56
	2100	73	68	63	58	54
	2200	77	71	66	61	57
	2300	81	75	69	64	60
	2400	85	79	73	68	63
	2500	89	83	77	71	66

3 x	W \ S	800	900	1000	1100	1200
		2000	117	108	100	93
	2100	122	113	105	97	90
	2200	129	119	110	102	95
	2300	135	125	116	107	99
	2400	135	131	122	113	104
	2500	135	135	128	118	109

3 x	W \ S	800	900	1000	1100	1200
	+	2000	76	70	65	60
	2100	80	74	68	63	59
	2200	84	77	72	66	61
	2300	85	81	75	70	65
	2400	85	85	79	73	68
	2500	85	85	83	77	71

4 x	W \ S	800	900	1000	1100	1200
	+	2000	117	108	100	93
	2100	120	113	105	97	90
	2200	120	119	110	102	95
	2300	120	120	116	107	99
	2400	120	120	120	113	104
	2500	120	120	120	118	109

3 x	W \ S	800	900	1000	1100	1200
		2000	87	81	75	69
+	2100	92	85	79	73	68
	2200	95	89	83	77	71
	2300	95	94	87	80	74
	2400	95	95	91	84	78
	2500	95	95	95	89	82

4 x	W \ S	800	900	1000	1100	1200
		2000	128	119	110	102
+	2100	130	125	116	107	99
	2200	130	130	121	112	104
	2300	130	130	127	118	109
	2400	130	130	130	124	115
	2500	130	130	130	130	120

3 x	W \ S	800	900	1000	1100	1200
		2000	93	86	80	74
	2100	98	91	84	78	72
	2200	103	95	88	82	76
	2300	108	100	93	86	79
	2400	113	105	97	90	83
	2500	115	110	102	95	88

4 x	W \ S	800	900	1000	1100	1200
		2000	134	124	115	106
	2100	141	130	121	112	104
	2200	148	137	127	117	109
	2300	150	144	133	123	114
	2400	150	150	140	129	120
	2500	150	150	147	136	126

